

CLAIMS

1. Motor vehicle (1) with a roof (2), which has at least one part (3) that can be fully opened, that can be fully moved to achieve this full opening, and that extends from an area adjacent to a windshield frame (4) to a rear, especially rigid, roof part (5), characterized by the fact that the rear section of the movable part (3) can be raised in such a way that the section of the movable roof part (3) that is located in front of the rear section that can be raised remains in a closed position.

2. Motor vehicle in accordance with Claim 1, characterized by the fact that the movable roof part (3) occupies the entire width between the upper edges of the side windows (7) of the motor vehicle (1).

3. Motor vehicle in accordance with Claim 1 or Claim 2, characterized by the fact that the movement of the rear section into and out of its raised position is possible while the vehicle is traveling.

4. Motor vehicle in accordance with any of Claims 1 to 3, characterized by the fact that the movable roof part (3) is

covered with a flexible covering (9).

5. Motor vehicle in accordance with any of Claims 1 to 4, characterized by the fact that to allow the rear section to be raised, a roof bow (27) is provided which grips beneath the rear section and is displaceably mounted on lateral frame parts (11) of the movable roof part (3).

6. Motor vehicle in accordance with Claim 5, characterized by the fact that at least one remotely controlled drive is provided for the displacement of the roof bow (27).

7. Motor vehicle in accordance with any of Claims 1 to 6, characterized by the fact that the rear roof part (5) is in the same position with the movable roof part (3) completely open and with the movable roof part (3) completely closed.

8. Motor vehicle in accordance with any of Claims 1 to 7, characterized by the fact that the rear roof part (5) can be lowered below a belt line (31) of the automobile body.

9. Motor vehicle in accordance with any of Claims 1 to 8, characterized by the fact that the rear roof part (5) covers a rigid roll bar (32).

10. Motor vehicle in accordance with any of Claims 1 to 9, characterized by the fact that the rear roof part (5) is at least partially movable to create an opening for the passage of

the fully movable roof part (3) to allow the latter to be opened.

11. Motor vehicle in accordance with Claim 10, characterized by the fact that the rear roof part (5) can be swung open about a rear axis (33) to create an opening for the passage of the roof part (3) and can be swung closed again over the opened roof part (3).

12. Motor vehicle in accordance with any of Claims 9 to 11, characterized by the fact that the opening for the passage of the movable roof part (3) is located between the rigid roll bar (32) and the opened rear roof part (5).